

Speaker Cable Meridian Mobile SP260; 2 x 6,00 mm²; PVC Ø 11,00 mm; grey

Art. No.: 460-0056

ANALOG

OFC



General Data

Article number :	460-0056
Name :	Meridian Mobile SP260
EAN :	4049371005340
Properties :	complies with IEC 60228/HD 383 S2
Properties :	Analog
Properties :	OFC oxygen free copper
Application area :	Stage / live
Application area :	Mobile outdoor / indoor
Application area :	Studio / Broadcast
Application area :	ELA 100 V
Application :	Speaker Cable
Colour :	grey
BPVo-Euroclass :	Fca

Test voltage [V] : 2000

Nominal voltage (power) [V] : 300

Technical Data

Construction :	(2LIY6,0mm ²)Y
Jacket material :	PVC
Jacket Ø [mm] :	11,00
Number of Channels (audio) :	1
Inner conductor (audio) :	2
Inner conductor (audio) [mm ²] :	6,00
Inner conductor Ø (audio) [mm] :	2,76
AWG (audio) :	10
Copper strands (audio) :	84
Copper strand Ø (audio) [mm] :	0,30
Conductor insulation material :	PVC
Conductor insulation Ø [mm] :	4,50
Weight per 1 m [g] :	215
Fire load per m [kWh] :	0,63
Style variant :	round
Packing :	100 m spool
Packing :	500 m spool
Temperature min. [°C] :	-30
Temperature max. [°C] :	70
Width [mm] :	11
[mm] :	11

Electrical Data

Capac. cond./cond. per 1 m (audio) [pF] :	125
Insulation resist. per 1 km [GΩ] :	0,005
Insulation resist. per 1 km (audio) [GΩ] :	0,005
Conductor resistance per 1 km [Ω] :	3,3